





The M.2 module is based on Artix-7 FPGA that provides bridging features between PCle and SD3.0 units to validate different memory densities of micro SD card. For host processor communication, the module is designed with 2-lane PCle Gen 2.0 interfaces. The module presents compact design, flexibility, and consumes low power. Since it is PCle backward compatible with the earlier version the user can integrate into existing systems with ease. The interface towards the SD card is realized by the SD protocol implemented in the FPGA.

HIGHLIGHTS

- 2280 M.2 M Keyed module form factor
- Complaint with SD3.0 standard specification
- Supports 2-Lane PCIe Gen2 link
- Supports both standard and highcapacity SD operations
- Supports data rate up to SDR 104/UHS-1

SPECIFICATIONS

Features

Supports legacy version of SD specification

ARTIX-7 FPGA to implement PCIe to SD3.0 bridge functionality

Micro SD slot to support the different memory density SD card

1x 10 pin GPIO Header to define functionality as per user requirement

Input Power: 3.3V@2.5A

Keying: M.2 Key M

Temperature Supported

-40C to +85C Industrial

Form Factor: 22mm x 80mm

Cooling: Conduction cooling using heat sink

on the FPGA device

SD Operations












iW PCIe to SD 3.0 M.2 Module Block Diagram



OS SUPPORT

Linux

DELIVERABLES

PCIe to SD 3.0 M.2 module

Heat sink

User Manual

ORDERING PART NUMBER

iW-M2SD-8GB-AR7-R1.0

iWave Systems Technologies is an ISO 9001:2015 certified company, head quartered in Bangalore India established in the year 1999. The company focuses on providing embedded solution and services for Industrial, Medical, Automotive and various other Embedded Computing applications. iWave Systems offers wide range of System On Modules and Single Board Computers built using wide range of CPU and FPGA SoC platforms with different form factors such as Qseven, SMARC, SODIMM and HPC by closely working with Tier-1 silicon companies such as NXP, Xilinx, Intel etc. iWave Systems offers various state of art ready ODM solutions such as Connected Telematic Control Unit / OBD II devices for the automotive edge analytics, Comprehensive ARINC818 solutions for the low latency Aerospace applications and Rugged IP rated performance scalable HMI solutions for Industrial applications.

iWave Systems also provides comprehensive Engineering design services involving Embedded Hardware, FPGA and Software development. iWave offers carrier board and custom hardware development with manufacturing and certification services. iWave's Hardware expertise spans complex board design up to 30 layers; Analog, Digital & RF Designs; FPGA Development up to 3+ million gates and VHDL / Verilog RTL Development & Verification. Our Software expertise ranges from OS Porting, Firmware & Device Drivers Development and Wireless & Protocol stacks.

Note: iWave reserves the right to change these specifications without notice as part of iWave's continuous effort to meet the best in breed specification. The registered trademarks are proprietary of their respective owners.

iW-PCle to SD 3.0 M.2 Module

The device can be ordered online from the iWave Website https://www.iwavesystems.com/product/pcie-to-sd-3.0-m.2-module/ Or from our Local Partners in your region http://www.iwavesystems.com/about-us/business-partner.html

iWave Systems Tech. Pvt. Ltd., 7/B, 29 Main, BTM Layout 2 nd Stage, Bangalore-560076 Email: mktg@iwavesystems.com

JAPAN

iWave Japan, Inc. 8F-B, Kannai Sumiyoshi Building, 3-29, Sumiyoshi-cho, Naka-ku, Yokohama, Kanagawa, Japan. mktg@iwavesystems.com

EUROPE

International Sales & Marketing Europe iWave USA Venkelbaan 55 2908KE Capelle aan den Ijssel The Netherlands info@iwavesystems.eu

USA

1692 Westmont Ave., Campbell, CA95008 **USA** info@iwavesystems.us