



KU19P Kintex UltraScale+ 3U VPX

Plug-In Module

iW-RainboW-G47V



iWave's 3U-VPX Plug-in Module based on Kintex UltraScale+ FPGA SOM, comprises of the Kintex UltraScale+ FPGA SOM and a 3U-VPX Carrier board. The SOM has a 64-bit Dual 4GB DDR4 RAM for the FPGA, featuring 8-bit ECC, and a 32-bit 2GB DDR4 RAM for the CPU, featuring 4-bit ECC.

The KU19P Kintex UltraScale+ 3U VPX Plug-In Module is equipped with VPX Connectors (P0+P1A & P1B+P2A) and an MT Ferrule Connector (P2B). This VPX Module offers a seamless Ethernet interface, delivering 1GBase-KX/10GBase-KR connectivity to the Backplane. Furthermore, there's an optional feature for PCIe Gen3 support through the VPX Connector's Data Plane and Expansion Switch.

APPLICATIONS: Military & Aerospace Systems, Embedded Computing, Data Center & Network Infrastructure, Sensor Networks and Telecommunications

iW-RainboW-G47V

HIGHLIGHTS


- Kintex UltraScale+ FPGA (KU19P)
- Compatible with KU115 & KU95
- Up to 1,843K Logic cells & 1,685K CLBs
- Dual ARM Cortex A7 @1.2GHz CPU
- 2GB CPU DDR4 with ECC (32bit)
- Dual 4GB FPGA DDR4 with ECC (64bit)
- Supports 1GBase-KX/10GBase-KR
- 10+ Years long term support

SPECIFICATIONS

KU19P – Kintex UltraScale+ FPGA
Compatible SoCs – KU115 & KU95
Up to 1,843K Logic cells & 1,685K CLBs
CPU:
Dual ARM Cortex A7 @1.2GHz
32KB Instruction and Data L1 cache
512KB Coherent L2 Cache
RAM Memory:
2GB DDR4 for CPU with ECC
4GB DDR4 (64 Bit) for FPGA from BANK 68,69,70
4GB DDR4 (64 Bit) for FPGA from BANK 71,72,73
On-SOM Flash:
128MB QSPI Flash
256MB NOR Flash
4MB MRAM
512KB SRAM
3U-VPX Front Panel Features:
USB3.0 & USB 2.0 through USB Type-C Connector
Debug UART through 3-Pin Header
1G Ethernet through 9-Pin Header
Other On-Board Features:
PCIe Gen2 through M.2(Key-M) Connector
Quad User LEDs
Temperature Sensor
Time Elapse Counter
Reset Switch
Clock Generators:
Clock Synthesizer with 10 Outputs
3 LVDS Clock Buffers for Transceivers reference Clocks
Slot Profile: SLT3-SWH-4F1U7U1J-14.8.7-n
Module Profile: MOD3-SWH-4F1U7U1J-16.8.7-n

3U-VPX Backplane Features
3U-VPX Connector (P0+P1A)
DP01[3:0] - 1G/2.5G/10G or PCIe Gen3 (using GTY Transceivers @ Upto 16Gbps/lane)
DS01[3:0] - 1G/2.5G/10G or PCIe Gen3 (using GTY Transceivers @ Upto 16Gbps/lane)
1 REF Clock Differential Pair Input
1 AUX Clock Differential Pair Input
I2C x 2
JTAG
Geographical Address (GA[0:4] & GAP)
Control Signals
12V - 7 Power Pins
3U-VPX Connector (P1B+P2A)
DP02[3:0] - 1G/2.5G/10G Ethernet (using GTY Transceivers @ Upto 16Gbps/lane)
DP03[3:0] - 1G/2.5G/10G Ethernet (using GTY Transceivers @ Upto 16Gbps/lane)
CPUTP[6:1] - 1G/2.5G/10G/25G Ethernet (using GTY Transceivers @ Upto 25Gbps/lane)
CsUTP01 - 1G/2.5G/10G/25G Ethernet (using GTY Transceivers @ Upto 25Gbps/lane)
MP01 and MP02
Maskable Reset
MT Ferrule Connector (P2B)
8 Fiber Optical Transceiver (4 x 2) Upto 28.125Gbps (Through two Firefly connectors)
Form Factor:
160mm X 100mm (3U-VPX Standard)
Power:
12V through 7 Power Pins of P0A
Compliance:
RoHS Compliant & REACH Compliant

KU19P Kintex UltraScale+ 3U-VPX Plug-in Module Block Diagram



OS SUPPORT

Linux 5.15.36
Xilinx-V2022.2

DELIVERABLES

KU19 Kintex UltraScale+ 3U VPX Plug-in Module
Petalinux BSP with Example FPGA Design
3U VPX Module Datasheet

OPTIONAL KITS/Modules

FireFly Optical Module*
9-Pin Header to Gigabit Magjack Cable
Custom JTAG Cable
Type-C loopback cable

CUSTOM DEVELOPMENT

BSP Development/OS Porting
Custom SOM/Carrier Development
Custom Application/GUI Development
Design Review and Support

iWave Systems Technologies is an ISO 9001:2015 certified company, head quartered in Bangalore India established in the year 1999. The company focuses on providing embedded solution and services for Industrial, Medical, Automotive and various other Embedded Computing applications. iWave Systems offers wide range of System On Modules and Single Board Computers built using wide range of CPU and FPGA SoC platforms with different form factors such as Qseven, SMARC, SODIMM and HPC by closely working with Tier-1 silicon companies such as NXP, Xilinx, Intel etc.

iWave Systems offers various state of art ready ODM solutions such as Connected Telematic Control Unit / OBD II devices for the automotive edge analytics, Comprehensive ARINC818 solutions for the low latency Aerospace applications and Rugged IP rated performance scalable HMI solutions for Industrial applications. iWave Systems also provides comprehensive Engineering design services involving Embedded Hardware, FPGA and Software development. iWave offers carrier board and custom hardware development with manufacturing and certification services. iWave's Hardware expertise spans complex board design up to 30 layers; Analog, Digital & RF Designs; FPGA Development up to 3+ million gates and VHDL / Verilog RTL Development & Verification. Our Software expertise ranges from OS Porting, Firmware & Device Drivers Development and Wireless & Protocol

*Optional items not included in the standard deliverables.

Note: iWave reserves the right to change these specifications without notice as part of iWave continuous effort to meet the best in breed specification. The registered trademarks are proprietary of their respective owners.

KU19P Kintex UltraScale+ 3U VPX Plug-in Module

The device can be ordered online from the iWave Website

<http://www.iwavesystems.com/webforms>

Or from our Local Partners in your region

<http://www.iwavesystems.com/about-us/business-partner.html>